

ID Material:
Rble: R. Antich
Revision: 0
Last updated: 01/08/2022

MM-MEX

MM-MEX is designed for heavy duty industrial brake applications. It consists a resin of impregnated textile based material with components. MM-MEX has an exceptional mechanical resistance, is fully cured and suitable for bonding and riveting.

Material data

Friction Properties (according graphics)

Static Friction Coefficient (15bar, from box):	0.37±0.05	μ
Static Friction Coefficient (15bar, 100°C):	0.47±0.05	μ
Dynamic Friction Coefficient:	see charts	
Wear Rate:	see charts	
T° Fading:	>250	°C

Physical properties

Hardness (DIN53505):	90±5	Shore-D
Specific Gravity (ASTM D792):	1.45±0.05	gr/cm3
Ignition Loss (ASTM D7348):	30±2	%
Acetone Extraction (ASTM D494):	3±0.2	%
Thermal Conductivity (ASTM E1952):	0.3±0.01	W/m°K

Mechanical properties

Tensile Strength (ASTM D638):	73±5	N/mm ²
Compressive Strength (ISO 844:2014):	361±5	N/mm ²
Shear Modulus (ASTM D2344-00):	3543±100	N/mm ²
Young Modulus (ASTM D638):	8432±100	N/mm ²

Recommended Working Values

T° Max. Continuous Operation:	200	°C
T° Max. Intermittent Operation:	250	°C

Material type : Rigid material

Appearance / Formats



Sheets

Applications

Forging machinery - Heavy duty static applications - Heavy-duty industrial machinery - Holding Mechanical Structures - Machinery Mining industries

Price Level : € € €

Reach (EC)1907/2023 - RoHS 2015/863/EU : Compliance

Others

Recommended Mating Surface:	Perlitic cast iron, hardness HB150-200
Recommended Adhesives:	Thermosetting adhesive
Oil Resistant:	Yes

